Gronkhile Heavy Duty Equipment Trailers

EXTRA WIDE & FLUSH DECK

50 Series

Flush Deck Design - 12,300 to 15,000 GVWR - Oak Floor - Channel Frame



Photo may be shown with options.

50 Extra Wide Series Trailer Models - Flush Deck			
Model Number	2650	2950	
Total GVWR (LBS)	12,300	15,000	
Total Axle Capacity (LBS)	12,000	14,000	
Payload Capacity (LBS)	10,000	12,000	
Standard Deck Width	84"	84"	
Standard Deck Length	16' + 2'BT	18'+ 2'BT	
Deck Height	24"	24"	
Deck Length Options	18' & 20'	20' & 22'	

FEATURES:

Extra Wide

Decks

- Solid 2" White Oak Deck Floor Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders Strength and Long Life
- Dexter Heavy Duty Drop Axles EZ Lube Grease Hubs Forward Self-Adjusting Brakes - Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Rugged "No Bend No Sag" Loading Ramps for Long Life
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking

Gronkhile Heavy Duty Equipment Trailers





Rugged Heavy Duty Dependable BUILT STRONGER TO LAST LONGER

Gronkhile FEATURES & SPECIFICATIONS

Capacity Features	2650	2950
GVWR - Lbs.	12,300	15,000
Total Axle Capacity - Lbs	12,000	14,000
Payload Capacity Lbs.	10,000	12,000
Deck Features	2650	2950
Standard Deck Width	84"	84"
Standard Deck Length	16' + 2'BT	18' + 2'BT
Standard Deck Height	24"	24"
Overall Width	102"	102"
Overall Length	22'	26'
Deck Width Options	No	Ne
Deck Length Options	18' & 20'	20' & 22'
Deck Flooring Material	20 & 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 22 20 20	
Axle & Brake Features	2650	2950
Dexter Heavy Duty Axle Size Lbs.	6,000	7,000
Dexter Heavy Duty Axle Type		
Slipper Spring Suspension	Straight Tandem Axles Yes – Multi Leaf	
Load Equalizers	Yes - Multi Leat Yes	
EZ Lube Grease Hubs	Yes	
Forward Self Adjusting Brakes All Wheel Electric Brakes	Yes 12" x 2"	
Wheel & Tire Features	2650 2950	
Radial Tires	ST225/75R 15 (D)	ST235/80R16 (E)
Tire Plies		
Disc Type Wheels	8 Ply 6-Bolt	10 Ply
Wheel Style		
Trailer Steel Construction Features	White Spoke 2650 2950	
Steel Frame Construction	5" C x 6.7	6"C x 10.5
Tongue Construction	6" Channel	6" x 10.5
Crossmember Size	Structural Channel – 3" x 4.1#	
Trailer Ramp Features		
FoldUp Heavy Duty Ramps		
Ramp Width	5' 14"	
EZ Slide Adjustable Ramp		
Ramps Lock n Store In Upright Position	Adjust from 80" to 6" Yes	
Ramp Lock System	Flat Bar Pin	
Additional Features	2650	2950
Heavy Duty Stake Pockets	6	8
Adjustable Coupler		
Ball Hitch	Heavy Duty 2 5/16" Or Adjustable Pintle Eye	
	2 5/16" Or Adjustable Pintle Eye 19" to 27"	
Hitch Height Range		
Drop Leg Jack Rating Diamond Plate Fenders with Backs	7K Lift-8K Static 10K Lift-12K Static	
	14 Gauge	
Step Tongue Design	Yes	
Sealed Beam LED Lighting	All LED lighting	
Wiring Protection	Steel Conduit	
Wiring Junction Box	Yes	
Safety Breakaway System	Yes	
Safety Chains and Hooks	Specifications subject to change without notice.	

Specifications subject to change without notice.

Cronkhite Trailers | 2212 Kickapoo Dr., Danville, IL 61822 | Phone: 217-443-3700 | Fax: 217-443-3778 | www.cronkhitetrailers.com rev04132019