

Green Climber
Challenge Accepted!



LV300Pro

LV300 PRO

REMOTE CONTROLLED SLOPE MOWER

SPECIFICATIONS LV300 PRO

| | |
|--------------------------|---|
| Engine | Yanmar 22.2 Kw |
| Horsepower | 30HP |
| Torque | 85.9Nm |
| Fuel type | Diesel |
| Fuel capacity (L) | 21 |
| Ground speed (Km/hr) | 9 |
| Standard Flail Weight | 130kg |
| Machine Weight only | 850kg |
| Flail Speed | 3000 rpm |
| Machine Height | 1040mm |
| Machine Length | 1840mm |
| Machine Width | 1140-1540mm |
| Main attachment pump | 42 lt/min @220bar - 11gal/min @ 3190psi |
| Service pump | 18 lt/min @ 180bar - 4.7gal/min @ 2610psi |
| Extendable undercarriage | (Closed) 1140 mm - (Open) 1540 mm |
| Attachment sideshifting | (Hydraulic) 400 mm + (Mechanical) 400 mm |

FEATURES

| | |
|--|--|
| Powerful 3-cylinder YANMAR DIESEL ENGINE | Patented undercarriage to climb steep slopes and anti-de-tracking system of the tracks. |
| Engine lubrication patented by MDB for continuous use on steep slopes of up to 60°. | The reversible fan and an oversized radiator allow for continuous work at full power also at high outside temperatures. |
| The integrated hydraulic side-shifting plate allows for lateral adjustment of the attachment of up to 400mm. | Onboard compartment with charger for the remote control. |
| Integrated cylinders allow for widening of the tracks from 1140mm up to 1540mm (patented system). | The totally hydraulic floating attachment plate of the mulcher allows the tool to remain constantly in contact with the floor which leads to a homogenous and superior cutting result. |



www.greenclimber.com.au

greenclimberaustralia

greenclimberau

©Copyright 2021. All rights reserved. Prices and Specifications subject to change without notice.