

3,500 to 5,200 GVWR - Low Deck - Drop Axle



Photo may be shown with options.

High Side Utility (HSU) Series - Single Axle

Model Number	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410E	HSU7412E
Total GVWR (LBS)	3,000	3,500	3,000	3,500	5,200	5,200
Total Axle Capacity (LBS)	3,500	3,500	3,500	3,500	5,200	5,200
Cubic Yard Capacity (LBS)	3	3.7	3.7	3.7	4.8	5.8
Bed Width	60"	60"	60"	60"	74"	74"
Bed Length	8'	8'	10'	10'	10'	12'
Bed Sides	22"	22"	22"	22"	22"	22"
Deck Height	15"	15"	15"	15"	15"	15"
Deck Width Options	None	None	None	None	None	None
Deck Length Options	None	None	None	None	None	None

FEATURES:

- Solid 2" Treated Pine Deck Floor – Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders – Strength and Long Life
- Dexter Heavy Duty Drop Axles – EZ Lube Grease Hubs – Forward Self-Adjusting Brakes
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

Capacity Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410E	HSU7412E
GVWR - Lbs.	3,000	3,500	3,000	3,500	5,200	5,200
Total Axle Capacity - Lbs.	3,500	3,500	3,500	3,500	5,200	5,200
Payload Capacity - Lbs.	1,700	2,200	1,600	2,100	3,600	3,500
Deck Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Standard Bed Width	60"	60"	60"	60"	74"	74"
Standard Bed Length	8'	8'	10'	10'	10'	12'
Bed Sides	22"					
Overall Width	82"			96"		
Overall Length	12'		14'			16'
Deck Width Options	No					
Deck Type	Drop Deck					
Deck Flooring Material	Pressure Treated Pine					
Axle & Brake Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Dexter Heavy Duty Axle Size Lbs.	3,500 lb.			5,200 lb.		
Heavy Duty Dexter Axle Type	Single 4" Drop Axle					
Slipper Spring Suspension	Yes - Multi Leaf					
Load Equalizers	N/A					
EZ Lube Grease Hubs	Yes					
Forward Self-Adjusting Brakes	N/A	Yes	N/A	Yes	Yes	Yes
Wheel & Tire Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Radial Tires	ST205/75R15			ST225/75R15		
Tires Load Range	C Tires			D Tires		
Tire Plies	6 Ply			8 Ply		
Disc Type Wheels	5-Bolt			6-Bolt		
Wheel Style	White Spoke					
Trailer Steel Construction Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Steel Frame Construction	3x2x¼ Angle		4x3x¼ Angle			
Tongue Construction	3" Channel		4" Channel			
Crossmember Size	3x2x¼ Angle		3" Channel			
Ramp Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Gate Ramp - Spring Assist	Yes - 4'					
Ramp Width	60"			74"		
Additional Features	HSU6008X	HSU6008E	HSU6010X	HSU6010E	HSU7410X	HSU7412E
Heavy Duty Stake Pockets	8 Total - 3 Each side / 2 Front					
D-Rings	4 - Inside the Bed Near Floor					
Adjustable Coupler	Heavy Duty Cast					
Hitch	Adjustable Height 2", 2 5/16" Ball Coupler or Pintle Eye					
Hitch Height Range	14" - 22"					
Drop Leg Jack Rating	7K					
Diamond Plate Fender w Full Back Plate	Yes					
Fender Step	Yes					
Sealed Beam LED Lighting	Stop - Tail - Turn Lights					
Wiring Protection	Rubber Backing					
Wiring Junction Box	N/A	Yes	N/A	Yes	Yes	Yes
Safety Breakaway System	N/A	Yes	N/A	Yes	Yes	Yes

Specifications subject to change without notice.